



ResiSHIELD DH Fire Sprinkler Pump Set

BS 9251:2021 compliant






A pre-assembled set, designed for the single dwelling domestic market.

PRODUCT OVERVIEW

- Domestic (Cat 1) application
- Housed within a mild steel enclosure
- Wall mountable
- Common models are available from stock
- BS 9251:2021 compliant

Key Features





REMOVABLE ENCLOSURE

Specification

Compact, fully pre-assembled fire pump sets to suit small to large domestic sprinkler systems.

PRODUCT OVERVIEW

- Housed within an aesthetically pleasing powder-coated mild steel enclosure, providing ultimate protection from accidental damage
- Removable front cover for easy maintenance access
- Wall mountable
- Fully compliant with BS 9251:2021 for Cat 1 sprinkler systems
- High-quality cast stainless steel manifold assembly
- Volt-free contacts included for fire alarm and range of faults
- Intuitive LCD controller with full number keypad makes set up and commissioning quick and user friendly
- Can be connected directly to the mains water supply (subject to local water authority approval)
- Common models are available from stock

RANGE PERFORMANCE

Flow range	30 - 200 l/min		
Pressure range	1 - 5 bar		
Max system pressure	10 bar		
Starting type	DOL		

MATERIAL SPECIFICATION


Manifold	Duplex stainless steel		
Union	Brass		
Non-return valve	Brass		
Pump casing	AISI 304 stainless steel		
Pump impellers	AISI 304 stainless steel		
Base plate/enclosure	Powder-coated mild steel		


DH03/05/10

DRAWINGS AND DIMENSIONS

Model no.	Motor nominal power (kW)	Supply voltage	FLC (A)	Suction size	Discharge size	Total weight (kg)
DH0302E-M	0.33	230/1/50	2.5	1 ¼" BSP	1" BSP	31
DH0303E-M	0.45	230/1/50	3	1 ¼" BSP	1" BSP	31
DH0304E-M	0.55	230/1/50	3.7	1 ¼" BSP	1" BSP	31
DH0305E-M	0.75	230/1/50	4.3	1 ¼" BSP	1" BSP	32
DH0502E-M	0.45	230/1/50	3	1 ¼" BSP	1" BSP	31
DH0503E-M	0.55	230/1/50	3.9	1 ¼" BSP	1" BSP	31
DH0504E-M	0.9	230/1/50	5.3	1 ¼" BSP	1" BSP	33
DH0505E-M	1.1	230/1/50	6.2	1 ¼" BSP	1" BSP	33
DH1002E-M	0.75	230/1/50	4.3	1 ½" BSP	1 ¼" BSP	32
DH1003E-M	1.1	230/1/50	6.3	1 ½" BSP	1 ¼" BSP	34
DH1004E-M	1.5	230/1/50	8.2	1 ½" BSP	1 ¼" BSP	37


All DH models use Direct On Line type starting.





DH03 Series


SINGLE PUMP CURVES




DH05 Series


DH10 Series


SINGLE PUMP CURVES





SINGLE PUMP CURVES







Let's talk about ResiSHIELD DH

01452 300110 ENQUIRIES@DUTYPOINT.COM DUTYPOINT.COM